

Side Sealer Shrink Wrap Machine

Model: V'S2

The VM Pack Continuous Side Sealing Shrink Wrap Machine, equipped with a servo motor controlled sealing bar mechanism, offers operation without product length limitations. This mechanism synchronizes with product flow to ensure uninterrupted operational continuity. The color touch control panel provides a user friendly interface, allowing quick and easy adjustments.

Its innovative design enhances accessibility, allowing operators to reach and intervene in all machine components more quickly and easily. This enables maintenance and service operations to be completed in minimal time, minimizing production downtime. Its ergonomic structure also saves space in production facilities, allowing more efficient use of available areas. For detailed technical information, model selection, or pricing inquiries, please contact us.



Feature	Description
Continuous Sealing Bar	The high speed continuous operation mechanism ensures consistent and orderly packaging of products.
Servo Motor Control	Enables precise and high speed cutting and sealing operations with servo driven control systems.
Color Touch screen Control Panel	User friendly interface allows for quick and easy adjustment of the machine settings.
Operating Modes	Sensor, measurement, and print mark(optional) modes adapt to various production needs.
Automatic Product Length Detection	Automatically detects product length for seamless packaging.
Motorized Width and Height Adjustment	Automatically adjusts to product dimensions.
Front-Rear Package Spacing	Adjustable in millimeters.
Recipe System	Allows for the saving of product parameters to enable quick recall and repeated use.
Product Counter	Counts the total number of packages produced during operation.
Motorized Film Waste Winding	Automatic winding system precisely collects shrink film waste generated during the packaging process. Speed is adjustable via drive control.
Motorized Film Unwinding	Automatically unwinds the shrink film from the roll during operation. Speed is adjustable via drive control.
Machine Material	The machine body is manufactured from steel construction and protected with electrostatic powder coating.
Warranty	1-year warranty, with 5-year spare parts availability.
CE Compliance	The machine is equipped with mechanical and electrical safety measures in accordance with CE directives.
Max. Product Dimensions	Width: 410 mm, Length: unlimited, Height: 200 mm
Max. Speed	35 meters/minute
Packaging Material	7–19 micron (POF), 35–50 micron (PE)
Max. Roll Width	650 mm
Air Pressure	6 Bar
Voltage	380V, 50/60Hz